

K-9000

“Touch the world best POS system, K-POS Series”

K-9000 is designed to provide outstanding performance for your business and to protect your business.




High Performance

- High-performance CPU loaded
- Vivid high-definition screen using LED technology
- Low-noise and low-heat using fan-less type



Stylish Design

- Polished appearance of having tender curve



Slim & Compact

- Ultra-thin and sleek exterior

Simple & Easy Maintenance

- Easy assembly & disassembly without tools
- Convenient access to Mother Board

K-9000

- Premium POS system designed for hospitality and retail
- Combined high technology and sleek design
- Maximum reliability
- Industry-leading durability and serviceability
- Vivid LED screen for the best view
- Tools-free maintenance with great ease



Product reliability & safety

Proven product reliability and safety through EMC test, KC, CE & FCC by Authorized Testing and Certification Bodies

Green IT

Low energy consumption can reduce unnecessary heat and expand the life span of POS components.



Specification

Item	Specification	
Main	Formfactor	170 mm(W) x 170mm(L): Embedded Mini ITX Platform
	CPU	Onboard Intel Celeron 1037U 1.8GHz (Dual Core)
	Chipset	Intel NM70 Express Chipset
	Memory	DDR3 SODIMM 2GB (up to 8GB by 2 x Slots)
	Storage	2.5" SATA-II 320GB HDD
Primary Display	LCD	15-inch TFT LED LCD (350cd), LVDS Interface
	Resolution	1024 x 768
	Touch	15-inch 5-Wire Resistive Frame Type, Serial Interface
I/O Port	Indicator	2 x LED
	Speaker	1 x 1W
	USB	6 x USB (Rear: 4 x USB, Side: 2 x USB)
	Serial	4 x RS-232C (3 x Powered DSUB-9, 1 x RJ-45) COM 1~4: 0/5/12V by BIOS select
	PS/2	1 x Keyboard or Mouse
	LAN	1 x Gigabit LAN
	VGA	1 x RGB
Power	DC-IN	External 60W Adapter Input AC 100~240V/50~60Hz, Output DC 12V/5A
	Audio	2 ports (1 x Mic-in, 1 x Line-out)
User Environment	Temperature	Operating -25 to 65, Storage -35 to 75
Size	Dimension	341 x 345 x 209 (WxDxH)
	Weight	6.6 Kg (without MSR) / 6.9 kg (with MSR)
Optional Peripherals	MSR	ISO 1,2,3 Tracks Reading
	OS	POSReady2009 / POSReady7
	Storage	SATA-III HDD 320GB / SSD 64GB
	2nd Display	15-inch LED LCD (1024 x 768) 9.7-inch TFT LCD (1024 x 768)

This specification can be changed without Prior notice

ver. KPOS_201312_EA

