

sewoo

Mobile Premium Series

SLK-TE25



- Printing speed and Compatibility
- Front paper loading & exit design
- Superior spill-proof with a sealed top.
- High speed printing at Max.7.9ips (200mm/sec.)
- Maximize productivity with Compact and Sleek design
- Reduce power consumption and cost through energy star certification.
- High reliability mechanism: 1.5 Million of Cutter life and 160km of TPH Life.



Barcode



Durable

80mm

Paper
Width



Easy
Loading



High
Speed



Compact
Design



Easy
Maintenance



Energy
Star

APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method

Direct thermal

Print Speed

Up to 7.9ips(200mm/sec)

Print Width

Up to 2.8" (72mm)

Resolution

180 dpi

Power

Power type : External SMPS

AC : 100~240Vac 50/60Hz

DC : 24Vdc / 1.75A

Sensor

Standard: Paper end, Paper low,
Cover open

Optional: Black mark

Reliability

TPH life : 160km

MCBF : 60 Million lines

Cutter life : 2.0 Million cuts

Drawer port

2 Circuit(24V, 1A Max.)



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)

4.42" x 7.87" x 4.92"
(112.5 x 200 x 125mm)

Weight

3.0lb(1.4Kg)



INTERFACES

Standard

USB(B type)

Option

Serial(RS-232C),

Parallel(IEEE1284),

Ethernet, Wi-Fi(802.11b),

Bluetooth Ver 2.1(Movon,iOS)

Bluetooth Ver 4.2(Movon,iOS)



CERTIFICATIONS

CE, FCC, KC, UL/cUL,

ENERGY STAR, Mfi



OPERATING CHARACTERISTICS

Operating Temperature

41 ~ 104°F(5 ~ 40°C)

Operating Humidity

35 ~ 80%

Storage Temperature

-4 ~ 140°F(-20 ~ 60°C)

Storage Humidity

10 ~ 90%



MEDIA CHARACTERISTICS

Media Type

Thermal receipt paper

Media Width

2.32", 3.14"(59, 80mm)

Media Core Diameter

0.4"(12.5mm)

Media Roll Diameter

3.2"(ø 83mm)

Thickness

0.06~0.09mm



SOFTWARE

Emulations

ESC/POS Command compatible

Drivers

Windows Driver(XP ~, Server2003 ~),
Windows CE & Mobile Driver (CE 4.2 ~,
Mobile 5.0 ~), Linux Driver, Mac Driver,
OPOS Driver, JavaPOS Driver, iOS SDK,
Android(6.0 ~) SDK, Windows SDK,
Windows CE SDK, Linux SDK



BARCODES

1D

EAN-8, EAN-13, Code 39, Code 93,
Code 128, ITF, UPC-A, UPC-E, Codabar
2D

QR, PDF417, Datamatrix



FONTS / GRAPHICS

Character Type

Font A(12x24), Font B(9x17),
Chinese(Traditional/Simplified, 24x24),
Korean(24x24), Japanese(24x24)

Characters per line (CPL)

Font A(12x24) : 42cpl,

Font B(9x17) : 56cpl,

Chinese/Korean/Japanese: 21cpl

Character set

95 Alphanumeric,

14 International,

128 x 18 Graphic



ACCESSORIES

Standard

Power Adaptor 24Vdc / 1.75A

Option

Melody Box



COLOR

Black, Ivory

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA_sales@miniprnter.com

México Office

Cuahtémoc, D.F. Mexico. CP 06500

T. +52-1-55-3232-9543 M. +52-1-55-143893

E. LA_sales@miniprnter.com

China Office

Shang hai shi, Song jiang qu

T. +86-177-1729-9100

E. sales@miniprnter.com

